

STANLEY

HAMMERS

LaBounty

STEALTH BREAKER SPECIFICATIONS

ITEM	UNITS	MB20EXS	MB30EXS	MB40EXS	MB50EXS	MB60EXS	MB70EXS	MB80EXS	MB100EXS
Impact Energy Class	ft-lb	1500	2000	3000	5000	6000	7500	8500	12000
	J	2034	2712	4068	6780	8136	10170	11526	16272
Oil Flow Range	gpm	15 - 25	20 - 30	24 - 35	32 - 45	37 - 50	45 - 63	51 - 67	55 - 80
	lpm	56 - 95	76 - 114	90 - 130	120 - 170	140 - 190	170 - 240	190 - 250	208 - 302
Maximum Hydraulic Pressure	psi	2500	2500	2500	2700	2700	2700	2700	2700
	bar	172	172	172	186	186	186	186	186
Blows Per Minute Range	blows per minute	360 - 800	500 - 700	400 - 600	400 - 500	300 - 450	300 - 400	280 - 370	230 - 320
Weight (with tool bit)	lb	1259	1898	2859	3964	4566	5803	6246	8799
	kg	571	861	1297	1798	2071	2632	2833	3991
Length (with tool bit)	in	71	77	89	96	105	110	117	128
	mm	1802	1962	2264	2451	2656	2783	2962	3241
Tool Working Length	in	18.3	19	25	29	31.5	33.6	35.2	35
	mm	466	486	646	727	800	853	895	890
Tool Diameter	in	3.3	3.9	5	5.5	5.9	6.1	6.5	6.9
	mm	84	100	127	140	150	155	165	175
System Relief	psi	3000	3000	3000	3100	3100	3100	3100	3100
	bar	207	207	207	214	214	214	214	214
Noise Level 85 dBA @ distance	ft	20 - 40	23 - 46	33 - 59	52 - 72	69 - 98	85 - 115	115 - 130	125 - 148
	m	6 - 12	7 - 14	10 - 18	16 - 22	21 - 30	26 - 35	35 - 40	38 - 45

CARRIER SIZE

Model	Excavator	Model	Backhoe
MB20EXS	10,000 - 25,000 lb 4,550 - 11,350 kg	MB20EXS	10,000 - 25,000 lb 4,550 - 11,350 kg
MB30EXS	18,000 - 35,000 lb 8,200 - 15,900 kg	MB30EXS	20,000 - 28,000 lb 9,100 - 12,700 kg
MB40EXS	30,000 - 50,000 lb 13,650 - 22,700 kg		
MB50EXS	41,000 - 65,000 lb 18,600 - 29,500 kg		
MB60EXS	46,000 - 68,000 lb 20,900 - 30,850 kg		
MB70EXS	58,000 - 85,000 lb 26,350 - 38,600 kg		
MB80EXS	60,000 - 100,000 lb 27,250 - 45,400 kg		
MB100EXS	80,000 - 130,000 lb 36,300 - 59,000 kg		

STEALTH BREAKER FEATURES

- S** **Silenced.** Noise suppression features make the new Stanley breakers some of the quietest on the market today.
- T** **Trimmed.** Narrower profile allows the breaker to work closer to the walls of a trench and give better visibility for the operator.
- E** **Enclosed Housing.** The powercell is suspended between bumpers eliminating damaging shocks transmitted to the carrier.
- A** **Armored Lower End.** The housing is double strength at the lower end of the breaker to fully protect the powercell.
- L** **Lighter Weight.** New generation stealth breakers are lighter in weight, allowing use of a lighter, less expensive carrier.
- T** **Two Moving Parts.** Translates into less maintenance, better performance, and significantly less service.
- H** **Hard Hitting.** Stanley breakers, pound for pound, are the hardest hitting breakers in their class.



MB60EXS Breaker
Mounting bracket not included, must be ordered separately.