

STANLEY

SHEARS



Model	JAW OPEN- ING in. / mm	JAW DEPTH in. / mm	WEIGHT lbs / kg	EXCAVATOR WGT (2ND MEM- BER) lbs / kg	EXCAVATOR WGT (3RD MEM- BER) lbs / kg
BLS 2000	15-20 / 381-508	19.5 / 495	3000 / 1364	-	40-65,000 / 18-29,484
BLS 3000	17-22 / 432-559	23 / 584	4800 / 2182	-	65-85,000 / 29-38,000
MSD 7R	10 / 254	11 / 279	1100 / 499	7500 / 3400	15,000 / 6804
MSD 1000	19 / 482	20 / 508	4000 / 1818	20,000 / 9090	35,000 / 15,909
MSD 1000R	19 / 482	20 / 508	4400 / 2000	23,000 / 10,454	40,000 / 18,144
MSD 1500	22 / 559	25 / 635	6600 / 3000	27,000 / 12,247	-
MSD 1500R	22 / 559	25 / 635	7100 / 3227	40,000 / 18,144	-
MSD 2000	28 / 711	29 / 737	8500 / 3864	42,000 / 19,051	75,000
MSD 2000-SL	28 / 711	29 / 737	8700 / 3955	42,000 / 19,051	75,000
MSD 2000R	28 / 711	29 / 737	10,200 / 4636	50,000 / 22,680	90,000
MSD 2000R-SL	28 / 711	29 / 737	10,200 / 4636	50,000 / 22,680	90,000
MSD 2500	32 / 813	34 / 864	11,600 / 5273	50,000 / 22,680	95,000
MSD 2500-SL	32 / 813	34 / 864	11,800 / 5364	50,000 / 22,680	95,000
MSD 2500R	32 / 813	34 / 864	14,500 / 6591	70,000 / 31,752	110,000
MSD 2500R-SL	32 / 813	34 / 864	14,700 / 6682	70,000 / 31,752	110,000
MSD 3000	35 / 889	38 / 965	13,300 / 6045	70,000 / 31,752	145,000
MSD 3000-SL	35 / 889	38 / 965	13,500 / 6136	70,000 / 31,752	145,000
MSD 3000R	35 / 889	38 / 965	16,500 / 7500	95,000 / 43,091	160,000
MSD 3000R-SL	35 / 889	38 / 965	16,700 / 7591	95,000 / 43,091	160,000
MSD 4500	38.5 / 978	43.5 / 1104	17,900 / 8136	90,000 / 40,824	165,000
MSD 4500-SL	38.5 / 978	43.5 / 1104	18,100 / 8227	90,000 / 40,824	165,000
MSD 4500R	38.5 / 978	43.5 / 1104	20,500 / 9318	110,000 / 49,896	185,000
MSD 4500R-SL	38.5 / 978	43.5 / 1104	20,700 / 9409	110,000 / 49,896	185,000
MSD 7500	43 / 1092	45 / 1143	25,400 / 11,545	135,000 / 61,235	consult factory
MSD 7500-SL	43 / 1092	45 / 1143	25,600 / 11,636	135,000 / 61,235	consult factory
MSD 7500R	43 / 1092	45 / 1143	29,500 / 13,409	160,000 / 72,575	consult factory
MSD 7500R-SL	43 / 1092	45 / 1143	29,700 / 13,500	160,000 / 72,575	consult factory